

5 0 3 5 1 2

Date of Registration

17-01-2011

Version

6 06/21/2023


MONTO
profesional


TYPE

Products for specific uses

LINE NIE

behead

DESCRIPTION

Fast-acting semi-gel stripper.
For removing all types of paint from any surface.
Biodegradable, non-toxic, methylene chloride free.

HOW TO USE

Exterior/Interior

Metal

Wood

Pavement

Concrete

Epoxy Paint

PROPERTIES

Optimal application
Open working hours
Easily removes paints by contact and light scraping, without generating dust
Removes paints and varnishes
Does not damage wood
Does not change its color
Acid-free
Alkaline-free
Methylene chloride free

TECHNICAL SPECIFICATIONS

Color	Translucent, milky white
-------	--------------------------

Finish	Transparent
--------	-------------

Specific gravity	0.96± 0.05 kg/l
------------------	-----------------

Viscosity	44 +/- 5 PO
-----------	-------------

Solids by volume	3± 1
------------------	------

Solids by weight	3± 1
------------------	------

Coverage rate	3-6 m ² /L
---------------	-----------------------

Dry to the touch	Working Time: 10-20 min.
------------------	--------------------------

Drying upon reapplication colors	(20°C RH: 60%): 6 hours
----------------------------------	-------------------------

SURFACE PREPARATION

New surfaces:

Not applicable

Restoration and maintenance

See the next section: Application.

HOW TO USE

Application notes

1. Homogenize the product slowly, using a spatula.
2. Apply with a brush or spatula, depending on the thickness of the layer to be removed, and leave to act for 10 to 20 minutes.

5 0 3 5 1 2

GEL REMOVER

Date of Registration

17-01-2011

Version

6 06/21/2023

MONTO
profesional

3. Remove the softened paint with a scraper or brush.
4. We strongly recommend testing the product on a small area before use to check compatibility. In case of If you have any questions, please consult the Technical Department.
5. Before recoating, it is recommended to thoroughly clean with clean water and completely dry the surface.

Thinner and cleaning agent

Water

How to use	Approximate dilution
Paint brush	Uso
roller	Uso
Palette / spatula	Uso

SYSTEM

Procedures depending on surface type

First	Intermediate	Finish
Montoxylo range		
MAX Not usually necessary		System Gama madera family 5
STD is not usually necessary		System Gama madera family 5
Polyurethane lacquers and varnishes		
MAX Quitamont gel	Quitamont gel	Sistema Gama Madera family 5
STD Quitamont gel		Sistema Gama Madera family 5
Nitrocellulose lacquers and varnishes		
MAX Quitamont gel	Quitamont gel	Sistema Gama Madera family 5
STD Quitamont gel		Sistema Gama Madera family 5
Enamels and synthetic varnishes		
MAX Quitamont gel	Quitamont gel	Sistema Gama Madera Family 5
STD Quitamont gel		Quitamont gel
Paints and water glazes		
MAX Quitamont gel	Quitamont gel	Sistema Gama Madera Family 5
STD Quitamont gel		Quitamont gel

SECURITY

Not eat, by not drink with not rinse heavy in water application.
 In the clean. case contact with and your eyes, leave TO in skillfully time
 Of children. not it to
 No sewage. DISPOSE

Store the product in a dry place, protected from the weather, at a temperature between 5 and 35°C.

For further information, please refer to the product safety data sheet.

NOTE

Maximum recommended storage period: 24 months from date of manufacture, in original packaging, perfectly closed, stored indoors, temperatures between 5°C and 35°C. to between and

The information presented here is based on our current knowledge, laboratory tests and practical use under specific conditions.

Since it is impossible to provide an adequate description for each type and condition of the supports to be painted, reproducibility is specific to each.
 not CAN guarantee a absolutely in case

5 0 3 5 1 2

Date of Registration

17-01-2011

Version

6 06/21/2023

MONTO
profesional

PACKAGING

0.375L, 0.75L, 4L