

# Nanomax Heavy Duty Degreaser Technical Data Sheet

**Effortlessly removes stubborn oil stains from paving, concrete, washed concrete, brick, screed and natural stone**

The quick and clean solution with simple application

**Oil Stain Remover** cleans **pavement, concrete, washed concrete, ceramic, screed and natural stone**. The surface must be dry. For coarse and fresh dirt, remove the oil puddle with **paper towels** or Nanomax Heavy Duty Degreaser.

## Instructions for use

Shake Nanomax Heavy Duty Degreaser well and apply to the dirty areas. It forms a thick film that adheres even to inclined surfaces. Leave to dry.

Leave on until Nanomax Heavy Duty Degreaser forms a solid white crust. Then brush or vacuum. For particularly stubborn stains, repeat the procedure. Waste containing oil must be disposed of in accordance with applicable regulations .

## CAREFUL

Not suitable for bitumen, asphalt or painted surfaces. Consumption: approx. 750 – 2250 ml/m<sup>2</sup>

## Description of special hazards

- H225 Highly flammable liquid and vapor .
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation .
- H319 Causes serious eye irritation .
- H336 May cause drowsiness and dizziness.
- H411 Toxic to aquatic life with long lasting effects.

## Precautionary measures

- P210 Keep away from heat, hot surfaces , sparks, open flames and other ignition sources. sources of ignition. No smoking.
- P261 Avoid breathing vapors/spray.
- P280 Wear protective gloves / protective clothing / eye protection / face protection .
- P301+P310 IF SWALLOWED : Immediately call a POISON CENTER TOXICOLOGIST / doctor.
- P331 DO NOT induce vomiting.

- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P235 Store in a well-ventilated place. Keep cool.

## Contain

Naphtha (petroleum), hydrotreated light, ethyl acetate, ≥30% aliphatic hydrocarbons, hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% n-hexane, hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes, hydrocarbons, C6-C7, isoalkanes, cycloalkanes, <5% n-hexane, hydrocarbons, C6, isoalkanes, <5% n-hexane, ethyl acetate.

## Emergency number for advice

NANOMAX ROMANIA

Store: Str. Bulevardul Petrolului no. 10, Ploiesti, Prahova Head

office: Str. Vornicei, no. 4, Ploiesti, Prahova Romania Tel: 0372

940 882 Fax: 0372

717 671 Mobile:

0726 632 423 Email:

[office@nano-auto.ro](mailto:office@nano-auto.ro)

## UFI code

836P-SXKQ-1106-14KA

## Additional Information

Shake well before use. For this reason, the container is not filled to the top. Keep refrigerated!