

## NANOMAX Wet Look

Water-based waterproofing for porous surfaces, with a wet look effect.

### Product Description

Nanomax Wet Look is a water-based waterproofing product, specially developed for the effective waterproofing and protection of natural stones, such as Karystos, Pelion, but also of structural surfaces, such as cement mortars, exposed concrete, plasters, floors stamped and paving stones. Thanks to its special composition, the product penetrates the applied surfaces, providing a wet look, while allowing the treated surfaces to breathe.

### Recommended use

Ideal for waterproofing natural stones and highlighting their natural colors, giving a "wet" look. It is applied to unpolished marble after testing and is ideal for porous surfaces, vertical or horizontal, both indoors and outdoors.

### BENEFITS

- ★ It highlights the natural look, providing a "wet" effect.
- ★ Permeability – Inorganic composition without resins, avoiding the formation of a superficial layer.
- ★ High penetration and durability against frost, moisture, UV radiation and adverse weather conditions
- ★ Strong water repellency
- ★ Prevents the development of fungi and mold

### Technical specifications

Type: Aqueous suspension

Appearance: Milky white

Density:  $1.00 \pm 0.05 \text{ g/cm}^3$

Application temperature: From 5°C to 35°C

Reapplication time: 1.5-2.5 hours @ 20°C  
pH:  $6.8 \pm 0.5$

Flow time (Ford cup N0 4): 11.6 sec

NanoPhos SA

PO Box 519, Sc i. & Te c h. Pa rk of La vrio ,1st Km. La vrio - Athene Ave

., 19500 To various, Greek

T. (+30) 22920 69312 | F. (+30) 22920 69303 | E. [info@nanophosc.com](mailto:info@nanophosc.com) | W. [www.NanoPhosc.com](http://www.NanoPhosc.com)

## NANOMAX Wet Look

### Water-based waterproofing for porous surfaces, with a wet look effect.

#### Surface preparation

All surfaces must be clean, dry and free of dust, oil, grease and other foreign residues or contaminants. Defects such as large cracks must be repaired before application of the material. Remove any mold or algae growth with Nanomax AntiAlg Cleaner

#### Application instructions

Shake well before use. Nanomax Wet Look is applied undiluted to dry surfaces, using a roller, brush or sprayer. It is recommended to apply two coats for a

For best results, especially on porous surfaces, apply the second coat while the first coat is still fresh.

Remove excess material 15 minutes after application. Time may vary depending on ambient temperature and humidity. Clean tools immediately after use with water.

#### Additional Information

For extremely porous surfaces, such as paving or cementitious materials, it is recommended applying one or two coats (depending on the porosity of the surface) of Nanomax ROCK to seal the surface. Let it cure for at least 24 hours before applying two coats of Nanomax Wet Look. The second coat of Nanomax Wet Look should be applied at half an hour after the first layer.

#### Coverage rate

8-15 m<sup>2</sup>/L, depending on the absorption of the applied surface.

#### Storage

Store in the original, closed packaging, in a well-ventilated area, at a temperature between 5°C and 35°C, away from sunlight and frost. Unfavorable storage conditions may affect the quality of the product.

#### Health and safety

Read the product label before use. The Safety Data Sheet is available on the NanoPhos website, [www.NanoPhos.com](http://www.NanoPhos.com), or upon request by contacting NanoPhos by email: [info@NanoPhos.com](mailto:info@NanoPhos.com) or by phone: (+30) 2292069312.

NanoPhos SA

PO Box 519, Sci. & Tech. Park of Lavrio, 1st Km. Lavrio - Athens Ave., 19500 Lavrio, Greece

T. (+30) 22920 69312 | F. (+30) 22920 69303 | E. [info@nanophos.com](mailto:info@nanophos.com) | W. [www.NanoPhos.com](http://www.NanoPhos.com)

## NANOMAX Wet Look

**Water-based waterproofing for porous surfaces, with a wet look effect.**

### Available packaging

↳ 5L Plastic Container

***Disclaimer: The recommendations in the Technical Data Sheet for the use of NanoPhos products are based on our scientific knowledge, laboratory studies and long-term experience. The information provided should be considered indicative and subject to review. constants, depending on the specific conditions and each practical application. Matching product must be checked in each case for the specific use, and the end user bears full and exclusive responsibility for any side effects that may arise from incorrect use of the product. This edition of this data sheet automatically cancels any previous edition relating to the same product. For more information, please contact NanoPhos: [info@NanoPhos.com](mailto:info@NanoPhos.com).***

Surfa Pore TM logo is a registered trademark of NanoPhos SA

NanoPhos SA