

681929

MONTO ECONATURE

Discharge date

04-01-2021

Version

3 26.04.2021

WALLS AND CEILINGS FAMILY
TYPE

MAT

DESCRIPTION

Eco-friendly, sustainable and certified European Ecolabel matt paint for interior walls and ceilings. Superior quality due to high washability, coverage and performance. Produces minimal emissions and is harmless to health and the environment. Does not generate unpleasant odors.

application

inside

Walls and ceilings
Cement mortarConcrete
Brick
and
so Gotelé (textured/splattered paint)

Drywall: PYL, PAL...

property



- Monolayer

- Gloss level: matt (according to UNE-EN 13300 standard, at 85° reflectance <10)

- Washability: Class 2 (according to standard UNE-EN 13300) - Meets the

ecological criteria set out in the European Commission Decision for the award of the Community eco-label for paints and varnishes.
interior -

Perfect finish - Dry

coverage of 98%, for a coverage of 9 m²/L, according to ISO 6504-3 tests carried out by an external laboratory. (This coverage may vary depending on the substrate, dilutions and colours.)

TECHNICAL SPECIFICATIONS

Color reference	WHITE ECONATURA QUANTITY
Finish	Pair
Specific gravity	1.52± 0.05 kg/l
Goo	75 +/- 10 PO
Solids by volume	41± 1
Solids by weight	62± 1
VOC	How. a/BA 75/30 (2007/2010): 0.06 g/l
Approximate yield per layer	9 m ² /L
Dry touch	(20°C RH: 60%): 1 hour
repaint	(20°C RH: 60%): 3-4 hours
colors	White and colors.

PREPARING THE SUPPORT

New substrates

Cement and concrete mortars:

1. Wait until completely hardened (min 30 days).
2. Clean any efflorescence with an abrasive blasting agent.
3. Neutralize alkaline surfaces.

681929

MONTO ECONATURE

Discharge date

04-01-2021

Version

3 26.04.2021



4. On polished surfaces: sand to open pores.

5. Clean the support of foreign objects.
6. Fix the removable supports with Fixative Emulsion or Fijamont.
7. Fill defects in the support (see family 6)

Plaster,

- brick, plaster: 1. Wait until completely dry (maximum humidity 20%).
 2. Clean the support of foreign objects.
 3. Clean any efflorescence with an abrasive blasting agent.
 4. Adjust the absorbency of the substrate with a sealant, fixative or a diluted layer of the same product. 5. On polished surfaces: sand to open the pores. 6. Fix the loose substrates with fixative emulsion or Fijamont.
 7. Fill defects in the support (see family 6)

PYL

- compartmentation: 1. Perform a general sanding of joints and grout attachment areas.
 2. Afterwards, clean to ensure the substrate is free of dust, grease and other contaminants.
 3. For application on colored plates prone to staining, apply Montoplac Stain Sealer.

Restoration and maintenance 1. Remove

- completely remove old paint in poor condition or poorly adhering.
 2. Glossy surfaces must be matted to ensure good adhesion.
 3. Painted substrates must be checked for strength and adhesion, their nature must be diagnosed to avoid possible incompatibilities, and dust and dirt must be removed before repainting.
 4. Fill the defects in the support with plaster (Plasmont).
 5. On walls with mold, pre-treat with Montolimp.

INSTRUCTIONS FOR USE

Application tips - Shake the product until perfectly homogenized.

- Dilute the product according to the porosity and condition of the substrate in the first layer.
 - Finish with one or more slightly diluted coats until the surface is completely covered.
- Do not apply the product at temperatures below 5°C or on surfaces exposed to strong sunlight.
- Do not wash until 24 days have passed.
 - Clean tools with water immediately after use.
 - For airless spraying, use nozzles with a 15 to 23 inch passage, pressure \geq 150 bar.

Solvent for dilution and cleaning

Water

Application method	Indicative dilution
Brush	0-5%
Roller	0-5%
Airless gun	10-30%
Air Mixing Gun	10-30%

SYSTEM

Processes by media type

Primer

Intermediate

Finish

Old painted interior work, in good condition

MAXIMAL

Diluted Econatura mounted as standard

Montó Econatura Diluted

Old painted interior work in poor condition

MAX Remover+Fixer

He founded Econatura

He founded Econatura

STD Removal + Diluted Amount of Econatura

He founded Econatura

Construction site

681929

MONTO ECONATURE

Discharge date

04-01-2021

Version

3 26-04.2021



MAX hairspray

He founded Econatura

He founded Econatura

Diluted Econatura mounted as standard

He founded Econatura

PYL partitioning

MAX Montó Econatura Diluted

He founded Econatura

He founded Econatura

Diluted Econatura mounted as standard

He founded Econatura

SECURITY

Do not eat, drink or smoke during application. In case of contact with eyes, rinse with plenty of clean water.

Keep out of reach of children. Do not empty into drains. Store in a dry, covered place at temperatures between 5 and 35°C. For further information, please refer to the product safety data sheet.

NOTE

Maximum recommended storage time: 24 months from manufacture, in original packaging, perfectly closed, covered and at temperatures between 5° and 35° C.

The data presented here are based on our current knowledge, laboratory tests and practical use in specific circumstances, using objective judgments. Due to the impossibility of establishing an adequate description for each type and condition of the different backgrounds to be painted, we cannot guarantee complete reproducibility for each specific use.

FORMATS

4 liters